

# Featured Products & Solutions



## iCAP for Real Time!

From Device to Dashboard  
Absolute Integration for  
smart management  
systems.

- Real time device management
- Dashboard centralized management
- Storage health monitoring & analysis
- Wide coverage, flexible deployment, easy access!



## M.2 (S42) 3IE4 on Display!

iSLC technology & up to 128GB! In-house developed firmware made for outdoor environments.

- Interface: SATA III 6.0 Gb/s
- Read/Write Speed: 540/400MB/s
- iDataGuard Technology
- Low power consumption
- DRAM-less, 100% data integrity
- Supports iSMART and iCAP



## Optimum DRAM Performance!

Compact memory module for extreme temperatures.

- JEDEC standard 1.2V(1.26V~1.14V) Power Supply
- 8 bit pre-fetch
- Bi-directional Differential Data Strobe
- Harsh Environments -40 to 85C
- 30μ" Gold Finger
- DDR4 Anti-sulfuration
- Optional conformal coating and Side-fill



EGPL-G2P1-C(W)2



EGPL-G2P1-C(W)1

## Solutions for Networking!

Next generation expansion card technology.

- Supports dual isolated GbE LAN ports, with PoE support
- Support 12V~24V power input via 4pin header
- IEEE 802.3af, up to 15.4W at 48V per PoE port
- 1.7KV HIPOT isolation, ESD Air-15kV, Contact-8kV protection
- Industrial temperature -40 °C to 85 °C